



Intel® Pentium® M Processor Low Voltage 738 for Embedded Computing

Product Overview

The Intel® Pentium® M processor low voltage 738 utilizes a new microarchitecture to meet the current and future demands of high-performance, low-power embedded computing, making it ideal for communications, transaction terminal, interactive client, and industrial automation applications. While incorporating advanced processor technology, it remains software-compatible with previous members of the Intel® microprocessor family.

The Intel Pentium M processor low voltage 738 is validated with the Intel® E7501 chipset and the Intel® 855GME chipset. The Intel E7501 chipset expands the processor's performance and I/O bandwidth capability for embedded computing, particularly within the communications market segment. It provides up to 4 GB single- or dual-channel DDR 200 memory, and features configurable, optional Error Correcting Code (ECC) operation.

The Intel 855GME chipset provides up to 2 GB of DDR 333 memory with configurable optional ECC operation. It also offers integrated graphics support via Intel® Extreme Graphics 2 Technology which provides enhanced graphics features including dual independent display support.

Product Highlights

- Available at 1.4 GHz with a 400 MHz processor side bus delivering up to 3.2 GB of data per second into and out of the processor
- Features a new microarchitecture designed from the ground up:
 - Dedicated hardware stack manager employs sophisticated hardware control for improved stack management



- Micro-ops fusion for improved instruction execution
- Advanced branch prediction capability
- 2 MB Level 2 Advanced Transfer Cache (ATC) delivers a high data throughput channel between the Level 2 cache and the processor core
- Second-generation Streaming SIMD Extensions (Streaming SIMD Extensions 2) capability adds 144 new instructions, including 128-bit SIMD integer arithmetic and 128-bit SIMD double-precision floating-point operation
- Manufactured on state-of-the-art 90nm process technology
- Support for uni-processor designs
- Fully compatible with existing Intel® Architecture-based software
- µFC-BGA 479 package
- Embedded life cycle support

Intel in
Communications



run
Better, faster
and further.

The Intel Pentium M processor low voltage 738/Intel E7501 chipset platform provides the performance and chipset I/O bandwidth to support multiple Gb Ethernet controllers in ultra-dense environments. The platform enables outstanding instruction execution/watt and is ideal for high-performance blades. The Intel Pentium M processor low voltage 738/Intel 855GME chipset platform provides a low-power solution while providing cutting-edge integrated graphics support via Intel Extreme Graphics 2 Technology.

Features

Efficient execution <ul style="list-style-type: none"> Advanced branch prediction Power optimized processor system bus Micro-op fusion Hardware stack manager 	<ul style="list-style-type: none"> Fast program execution Low exception handling overhead Excellent packet manipulation: load, store Low context switching latency
Power-optimized circuitry <ul style="list-style-type: none"> Cache and processor bus power management Next-generation Intel SpeedStep® technology 	<ul style="list-style-type: none"> Low average power consumption Multiple frequency/voltage operating points
Data supply <ul style="list-style-type: none"> Large L1/L2 caches 	<ul style="list-style-type: none"> Fast large-table look-ups: routing tables
High I/O bandwidth <ul style="list-style-type: none"> Intel® E7501 chipset supports up to six PCI-X segments 	<ul style="list-style-type: none"> High packet throughput and processing
Graphics support <ul style="list-style-type: none"> Intel® 855GME chipset provides integrated graphics support via Intel® Extreme Graphics 2 Technology 	<ul style="list-style-type: none"> Cutting-edge graphics performance while reducing system cost

Intel® Pentium® M Processor Low Voltage 738 for Embedded Computing

Product Number	Core Speed	External Bus Speed	L2 Cache	Thermal Design Power	VID	Tjunction	Package
RJ80536LC0172M	1.4 GHz	400 MHz	2 MB	10 watts	1.116V	100° C	µFC-BGA 479

Intel Access

Developer's Site:	developer.intel.com
Embedded Intel® Architecture Home Page:	www.intel.com/design/intarch
Intel Technical Documentation Center:	www.intel.com/go/techdoc (800) 548-4725 7 a.m. to 7 p.m. CST (U.S. and Canada) International locations please contact your local sales office.
General Information Hotline:	(800) 628-8686 or (916) 356-3104 5 a.m. to 5 p.m. PST

For more information, visit the Intel Web site at: developer.intel.com

UNITED STATES AND CANADA
Intel Corporation
Robert Noyce Bldg.
2200 Mission College Blvd.
P.O. Box 58119
Santa Clara, CA 95052-8119
USA

EUROPE
Intel Corporation (UK) Ltd.
Pipers Way
Swindon
Wiltshire SN3 1RJ
UK

ASIA-PACIFIC
Intel Semiconductor Ltd.
32/F Two Pacific Place
88 Queensway, Central
Hong Kong, SAR

JAPAN
Intel Kabushiki Kaisha
P.O. Box 115 Tsukuba-gakuen
5-6 Tokodai, Tsukuba-shi
Ibaraki-ken 305
Japan

SOUTH AMERICA
Intel Semicondutores do Brazil
Rue Florida, 1703-2 and CJ22
CEP 04565-001 Sao Paulo-SP
Brazil

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER, AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. Intel products are not intended for use in medical, life saving, or life sustaining applications. Intel may make changes to specifications and product descriptions at any time, without notice.

Copyright © 2004 Intel Corporation. All rights reserved.

Intel, the Intel logo, Pentium and SpeedStep are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Printed in USA

0604/DLC/OCG/XX/PDF

 Please Recycle

302905-001EN

